

LF220 RESIN (5 MIN)

Page: 1

Compilation date: 16/01/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: LF220 RESIN (5MIN)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Cyanotec Ltd

Bay 2 Building 62 Third Avenue Pensnett Trading Estate Kingswinford DY6 7XT Tel: >>>

Email: tim@cyanotec.com

1.4. Emergency telephone number

Emergency tel: 08456183120

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP:	Xi: R36/38; Sens.: R43; N: R51/53	
Classification under CLP:	Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317	
Most important adverse effects: Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic t		
	organisms, may cause long-term adverse effects in the aquatic environment.	

2.2. Label elements

Label elements:

Hazard statements:	H315: Causes skin irritation.		
	H317: May cause an allergic skin reaction.		
	H319: Causes serious eye irritation.		
	H411: Toxic to aquatic life with long lasting effects.		
Signal words:	Warning		
Hazard pictograms:	s: GHS07: Exclamation mark		
	GHS09: Environmental		



LF220 RESIN (5 MIN)

Page: 2

	1 490. 2	
Precautionary statements:	P264: Wash soap and water thoroughly after handling.	
	P273: Avoid release to the environment.	
	P280: Wear protective gloves/protective clothing/eye protection/face protection.	
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove	
	contact lenses, if present and easy to do. Continue rinsing.	
	P321: Specific treatment (see instructions on this label).	
	P332+313: If skin irritation occurs: Get medical advice/attention.	
Label elements under CHIP:		
Hazard symbols:	Irritant.	
	Dangerous for the environment.	
	*	
Risk phrases:	R36/38: Irritating to eyes and skin.	
	R43: May cause sensitisation by skin contact.	
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic	
	environment.	
Safety phrases:	S2: Keep out of the reach of children.	
	S28: After contact with skin, wash immediately with plenty of soap and water.	
	S37/39: Wear suitable gloves and eye / face protection.	
	S61: Avoid release to the environment. Refer to special instructions / safety data sheets.	
2.3. Other hazards		
	This product is not identified as a PBT/vPvB substance.	
Section 3: Composition/information on ingredients		

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	CHIP Classification	CLP Classification	Percent
500-033-5	25068-38-6	Xi: R36/38; Sens.: R43; N: R51/53	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	>90%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

LF220 RESIN (5 MIN)

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

LF220 RESIN (5 MIN)

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area. The floor of the storage room must be
impermeable to prevent the escape of liquids.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Protective gloves.Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid	
Colour:	Pale yellow	
Odour:	Characteristic odour	
Evaporation rate:	Negligible	
Oxidising:	No data available.	
Solubility in water:	Insoluble	
Viscosity:	Viscous	
Boiling point/range°C:	>85 Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available. upper:	No data available.
Flash point°C:	>80 Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	>300 Relative density:	1.1
pH:	n/a	

LF220 RESIN (5 MIN)

Page: 5

VOC g/I: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

LF220 RESIN (5 MIN)

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

LF220 RESIN (5 MIN)

Page: 7

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No		
	453/2010.	
	* indicates text in the SDS which has changed since the last revision.	
Phrases used in s.2 and s.3:	H315: Causes skin irritation.	
	H317: May cause an allergic skin reaction.	
	H319: Causes serious eye irritation.	
	H411: Toxic to aquatic life with long lasting effects.	
	R36/38: Irritating to eyes and skin.	
	R43: May cause sensitisation by skin contact.	
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic	
	environment.	
Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive		
	and shall be used only as a guide. This company shall not be held liable for any	
	damage resulting from handling or from contact with the above product.	